Heaps

Tiziana Ligorio
Hunter College of The City University of New York

Announcements

Please fill out the teacher evaluation form, thank you!

- Smartphone: www.hunter.cuny.edu/mobilete
- Computer: www.hunter.cuny.edu/te

Heap

A **Heap** is a complete binary tree that is either

- Empty or
- Its **root** contains a value **≥** (or ≤) both of its **children** and has **heaps as subtrees**

Heap

A special binary tree:

- Ordered in a weaker sense
- Always a **complete** binary tree

MaxHeap



MinHeap



Implementation

How would you implement it???

Implementation

How would you implement it???

Insight: it is **always complete**

Implementation



Implementation




```
root_ = items_[0]
items_[i] left_child = items_[2 * i + 1]
items_[i] right_child = items_[ 2 * i + 2]
items_[i] parent = items_[(i-1)//2]
```

floor division

MaxHeap



Priority Queue



Retrieve

Can only retrieve max/min item

Stored at root

O(1)

Remove

Remove max/min item (the root)

Must retain Heap

- Heap ordering property
- Complete

Remove



What element do we remove?

Remove



What element do we remove?

What node do we remove?

Remove



What element do we remove?



Remove this node form complete tree

Remove





Complete

Not Heap



heapRebuild

Remove

Complete

Trickle down by swapping
Compare left and right



heapRebuild

Remove

Complete

<u>Trickle down</u> by swapping
Compare left and right

Heap!





Remove



Remove



Remove





Remove









heapRebuild

Remove

Complete

Trickle down by swapping
Compare left and right






```
items_[i] left_child = items_[2 * i + 1]
items_[i] right_child = items_[ 2 * i + 2]
```

heapRebuild

Remove

Complete

Trickle down by swapping
Compare left and right



Not Heap



1	9	6	2	3
1	9	6	2	3

```
items_[i] left_child = items_[2 * i + 1]
items_[i] right_child = items_[ 2 * i + 2]
```

heapRebuild

Remove

Complete

Trickle down by swapping
Compare left and right





1	9	6	2	3
1	9	6	2	3

```
items_[i] left_child = items_[2 * i + 1]
items_[i] right_child = items_[ 2 * i + 2]
```

heapRebuild

Remove

Complete



Trickle down by swapping
Compare left and right



Trickle down by swapping
Compare left and right

1	9	6	2	3
1	9	6	2	3
9	1	6	2	3

```
items_[i] left_child = items_[2 * i + 1]
items_[i] right_child = items_[ 2 * i + 2]
```

heapRebuild

Remove

Complete



Trickle down by swapping
Compare left and right



Trickle down by swapping
Compare left and right



Heap!

1	9	6	2	3
1	9	6	2	3
9	1	6	2	3
9	3	6	2	1

heapRebuild

Remove

Complete



Trickle down by swapping
Compare left and right



Trickle down by swapping
Compare left and right



Heap!

O(logn)

1	9	6	2	3
1	9	6	2	3
9	1	6	2	3
9	3	6	2	1

Add



Add



15 **Where do we add?**



Add




```
items_[i] left_child = items_[2 * i + 1]
```

Add





Add






```
items_[i] parent = items_[(i-1)//2]
```

Add



10	9	6	2	3	15
10	9	15	2	3	6

```
items_[i] parent = items_[(i-1)//2]
```

Add



10	9	6	2	3	15
10	9	15	2	3	6

```
items_[i] parent = items_[(i-1)//2]
```

Add



10	9	6	2	3	15
10	9	15	2	3	6

```
items_[i] parent = items_[(i-1)//2]
```

Add



10	9	6	2	3	15
10	9	15	2	3	6
15	9	10	2	3	6

```
items_[i] parent = items_[(i-1)//2]
```

Add



Heap!

O(logn)

10	9	6	2	3	15
10	9	15	2	3	6
15	9	10	2	3	6

```
items_[i] parent = items_[(i-1)//2]
```

heapCreate



heapCreate






```
for(int i=(itemCount//2)-1; i >=0; i--)
{
    heapRebuild(i);
}
```

heapCreate






```
for(int i=(itemCount/2)-1; i >=0; i--)
{
    heapRebuild(i);
}
```

heapCreate






```
for(int i=(itemCount/2)-1; i >=0; i--)
{
    heapRebuild(i);
}
```

heapCreate






```
for(int i=(itemCount/2)-1; i >=0; i--)
{
    heapRebuild(i);
}
```

heapCreate



6	3	5	9	2	10
6	3	10	9	2	5
6	9	10	3	2	5



```
for(int i=(itemCount/2)-1; i >=0; i--)
{
    heapRebuild(i);
}
```

heapCreate



6	3	5	9	2	10
6	3	10	9	2	5
6	9	10	3	2	5



```
for(int i=(itemCount/2)-1; i >=0; i--)
{
    heapRebuild(i);
}
```

heapCreate



6	3	5	9	2	10
6	3	10	9	2	5
10	9	6	3	2	5



```
for(int i=(itemCount/2)-1; i >=0; i--)
{
    heapRebuild(i);
}
```

heapCreate



Heap!

6	3	5	9	2	10
6	3	10	9	2	5
10	9	6	3	2	5

n/2 heapRebuild

```
for(int i=(itemCount/2)-1; i >=0; i--)
{
    heapRebuild(i);
}
```

Heapsort

Heapsort

Given an unsorted array:



- heapCreate
- last = n - 2
- repeat:
    - swap items[0] with items[last+1]
    - last--
    - heapRebuild





Heapsort

Given an unsorted array:

- heapCreate
- last = n - 2
- repeat:
    - swap items[0] with items[last+1]
    - last--
    - heapRebuild



Heapsort



10	9	6	3	2	5

Heapsort





Heapsort





heapRebuild

Heapsort





Heapsort





Heapsort





heapRebuild

Heapsort





heapRebuild

Heapsort





Heapsort





Heapsort





heapRebuild

Heapsort





heapRebuild

Heapsort





Heapsort





Heapsort





heapRebuild

Heapsort





heapRebuild

Heapsort





Heapsort





Heapsort





Heapsort



Heapsort

Sorted



Heapsort Analysis

1. heapCreate -> O(n logn)

2. heapRebuild -> O(logn) repeated for each of the n sorted items

O(n logn) + O(n logn) = **O(n logn)**

Like MergeSort but no extra space needed!